

Laser Measuring Device LE-100 Profibus (PNO)



- Robust
- Measurement of Linear Movement
- Non Contact Distance Measurement
- Measuring Distance Up To 100 m
- Interface : Profibus-DP
- Parametrizable via PROFIBUS,
according to PNO-profile CLASS2

Electrical Data

8

Measurement Principle.....	Phase shift measurement
Range (LE100 to Reflector).....	0.2 to 100 m
Resolution	0.5 mm
Supply Voltage	18-27 V DC ± 5 %, 24 V DC ± 5 % (device with heating)
Power Dissipation (No Load).....	< 6 Watt, < 60 Watt (device with heating)
Light Source.....	Laser Diode (Red Light)
Wave Length λ	670 nm
Maximum Laser Power	$P \leq 1$ mW
Laser Protection Class.....	2 (IEC 825)
Lifetime (25°C / 77°F).....	50 000 h
Light Receiver	Photo Diode
Measurement Value Output.....	$\geq 0,001$ mm
Measurement Value Output / Cycle Time.....	1000 values per second
Reproduction.....	± 2 mm
Programmable via RS485	PC IBM compatible EPROG software / Profibus-DP
Profibus-DP Interface:.....	PROFIBUS-DP acc. to DIN 19245 Part 1-3
Output code:.....	Binary
Baud rate:	9,6 kBaud to max. 12 Mbaud
Special features:	Programming is performed via the parameterization message at the start-up of the encoder or PROFIBUS-DP master
Station addresses:	3 – 99
Inputs	
Preset 1	Electronic adjustment
Logic Levels	"0" < + 2 V DC, "1" > + 8 V DC, max. 30 V DC
Pin Configuration	Upon Request

Environmental Data

Electromagnetic compatibility	EN 61000-4-2 (IEC-801-2) / EN 61000-4-4 (IEC-801-4)
Operating Temperature	0° to 50°C (32° F to 122° F), -30° to +50°C (device with heating)
Thermal drift.....	1 ppm / °C
Storage temperature range.....	-20° to 75°C (- 4° F to 167° F)
Relative Humidity.....	98 % (non condensing)
* Protection Class.....	IP 65 (DIN 40 050)

* The protection class of the device can be effected by the type of cable and connector used.

Mechanical Data

Vibration (50-2000 Hz Sinusoidal)	DIN IEC 68-2-6
Shock (11ms)	DIN IEC 68-2-27
Mechanical Special Types	Upon Request
Connection.....	Screw Terminals, 3 x PG 9

Dimension drawing

